

STANDARD VERSION

Fully upholstered seat and back. Backrest 39 cm.

Including black armrests.

4-leg frame, round tube. Standard version chrome-plated, with plastic floor protectors.

OPTIONS

- Upholstery fabric price group 2Upholstery fabric price group 3
- Upholstery fabric price group 4
- Felt floor protectors

LOAD CAPACITY

110 kg

SIZES

CHAIR WIDTH	60 cm
CHAIR HEIGHT	83 cm
SEAT HEIGHT	46 cm
CHAIR DEPTH	57 cm
STACKABILITY	-
WEIGHT	8 kg

BENEFITS/SPECIALS



Ergonomically shaped



Comfortable armrests



Robust 4-leg frame



Stackable up to 4 chairs

FABRIC PROPERTIES

INTENSIVE Price group 1

100% polyester | flame retardant according to EN 1021 1&2 | 250 g/m2 +/-5% | 100,000 Martindale tours | linting 5 | ÖKO-Tex 100

SKANDIA Price group 1

100% polyester | flame retardant according to EN 1021 1 | 245 g/m2 +/-5% | 70,000 Martindale tours | linting 4-5 | ÖKO-Tex 100

FLEECE Price group 1

100% polyester | flame retardant BS 5852:Part1:1979 (cigarette) | 402 g/m2 | 100,000 Martindale tours | linting 4 | ÖKO-Tex 100

TAFF B1 Price group 2

100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B1 | 260 g/m2 +/-5% | 70,000 Martindale tours | linting 5 | ÖKO-Tex 100

WOOL Price group 3

 $100\% \ wool \ | \ flame \ retardant \ according \ to \ EN \ 1021 \ 1\&2 \ | \ 460 \ g/m2 \ +/-5\% \ | \ 35,000 \ Martindale \ tours \ | \ linting \ 4 \ | \ tested \ for \ for$ harmful substances

PROTEX Price group 3
surface 100% vinyl / fabric 100% polyester | flame retardant according to EN 1021 1&2, DIN 4102 B2 | 685 g/m2 | 300,000
Martindale tours | no linting | wipeable with soap and water, water repellent, antibacterial, anti-static, stain resistant to blood and urine, mold resistant backing and surface, resistant to disinfectants

ARTIFICIAL LEATHER Price group 3

surface 100% polyurethane/ fabric 65% polyester, 35% cotton | flame retardant according to EN 1021-1 | 435 g/m2 \pm +/-10% | 100,000 Martindale tours | no linting | tested for harmful substances

ARTIFICIAL LEATHER B1 Price group 4
85% PVC compound, 15% cotton knit | flame retardant according to EN 1021 1&2, DIN 4102 B1 | weight 780+/-50 g/m2 |
75,000 Martindale tours | no linting | tested for harmful substances | resistant to blood and urine, resistant to disinfectants